

What is claimed is:

1. A gas sensor measuring a given component content in a gas comprising:

5 a housing;

a sensing unit having a length disposed in said housing, said sensing unit having defined in a first end portion thereof a reference gas chamber to be filled with a reference gas used in providing a sensor signal through a lead which is employed in determining the

10 given gas component content in the gas;

a first metallic cover installed on said housing to cover a second end portion of said sensing unit;

a second metallic cover installed on a periphery of said first metallic cover;

15 a first vent formed in said first metallic cover;

a second vent formed in said second metallic cover which communicates with said first vent to admit the reference gas into the reference gas chamber through a reference gas passage; and

an insulating member disposed in said first metallic cover, 20 having formed therein a hole through which the lead passes to connect with said sensing unit, said insulating member being made of a cylindrical porcelain having an outer peripheral wall which is substantially circular in cross section and which defines the reference gas passage.

25

2. A gas sensor as set forth in claim 1, wherein said insulating

member has a first end surface and a second end surface opposed to the first end surface in a longitudinal direction of the gas sensor parallel to the length of said sensing unit, said insulating member having a through hole extending in a direction of the first end surface to the second end surface to define a portion of the reference gas passage.

3. A gas sensor as set forth in claim 1, wherein said insulating member is arranged in alignment with said sensor unit and has a first end surface and a second end surface closer to said sensor unit, said insulating member having a groove formed in the outer peripheral wall which extends from the first vent to the first end surface to define a portion of the reference gas passage.

4. A gas sensor as set forth in claim 3, wherein said insulating member has a small-diameter portion formed closer to the first end surface and a large-diameter portion continuing from the small-diameter portion, and wherein if a length of the small-diameter portion in a direction is defined as $L1$, a distance $L2$ between the large-diameter portion and an upstream end of the groove facing the first vent lies within a range of $L1/5$ to $L1/2$.

5. A gas sensor as set forth in claim 3, wherein the first vent has a diameter R in the longitudinal direction of the gas sensor, and a distance between a point on a periphery of the first vent closest to the second end surface of said insulating member and an upstream

end of the groove facing the first vent is greater than or equal to $R/3$.

6. A gas sensor as set forth in claim 1, wherein said insulating member is arranged in alignment with said sensor unit and has a first end surface and a second end surface closer to said sensor unit, said insulating member having a groove formed in the outer peripheral wall which extends from the first vent to the second end surface to define a portion of the reference gas passage.

7. A gas sensor as set forth in claim 3, wherein if a plane tangent to a periphery of said insulating member is defines as P , a plane passing through the deepest point of the groove in parallel to the plane P is defined as $P1$, and a plane passing in parallel to the plane P through the center of the through hole formed in said insulating member is defined as $P2$, a distance $S1$ between the planes P and $P1$ is smaller than or equal to a distance $S2$ between the planes P and $P2$.

8. A gas sensor as set forth in claim 6, wherein if a plane tangent to a periphery of said insulating member is defines as P , a plane passing through the deepest point of the groove in parallel to the plane P is defined as $P1$, and a plane passing in parallel to the plane P through the center of the through hole formed in said insulating member is defined as $P2$, a distance $S1$ between the planes P and $P1$ is smaller than or equal to a distance $S2$ between the planes P and $P2$.

9. A gas sensor as set forth in claim 1, wherein if a width of the reference gas passages defined on the outer peripheral wall of said insulating member is defined as $H1$, and a diameter of said
 5 insulating member is defined as $H2$, a condition of $H1 \leq H2 / 2^{1/2}$ is satisfied.

10. A gas sensor as set forth in claim 1, wherein said insulating member has formed therein a plurality of lead holes through which
 10 leads pass to connect with said sensing unit, and wherein the reference gas passage is defined at a location where a line passing through a center of said insulating member between adjacent two of the lead holes intersects the outer peripheral wall of said insulating member.

15 11. A gas sensor as set forth in claim 1, wherein the reference gas passage is defined by a hole formed in said insulating member which extends from a portion of the outer peripheral wall of said insulating member facing the first vent and communicates with the hole
 20 through which the lead passes.

12. A gas sensor as set forth in claim 2, wherein said insulating member has formed therein a plurality of lead holes extending in the longitudinal direction of the gas sensor through which leads pass to
 25 connect with said sensing unit, and wherein said insulating member has formed therein a lateral hole extending between the lead holes in

communication with the through hole extending in the direction of the first end surface to the second end surface of said insulating member to define the reference gas passage.

- 5 13. A gas sensor as set forth in claim 1, wherein said insulating member includes a small-diameter portion and a large-diameter portion continuing from the small-diameter portion and has a chamber formed in said insulating member, and wherein the reference gas passage is defined by a through hole formed in said
 - 10 insulating member which extends from a portion of the outer peripheral wall facing the first vent to the chamber through the small-diameter portion and the large-diameter portion.
14. A gas sensor as set forth in claim 1, wherein said insulating
 - 15 member is arranged in alignment with said sensor unit and has a first end surface and a second end surface closer to said sensor unit, and wherein the reference gas passage is defined by an inner wall of said first metallic cover and a surface of the outer peripheral wall of said insulating member tapering off to the first end surface.
- 20 15. A gas sensor forth in claim 1, wherein said insulating member is arranged in alignment with said sensor unit and has a first end surface and a second end surface closer to said sensor unit, and wherein the reference gas passage is defined by an inner wall of
 - 25 said first metallic cover and a first and a second annular step formed on the outer peripheral wall of said insulating member, the first

annular step being smaller in diameter than the second step.

16. A gas sensor as set forth in claim 2, wherein the reference gas
passage is defined by a hole formed in said insulating member which
5 extends from a portion of the outer peripheral wall of said insulating
member facing the first vent and communicates with the hole
through which the lead passes.

10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995